


(12) UK Patent Application (19) GB (11) 2 309 256 (13) A**(43) Date of A Publication 23.07.1987****(21) Application No 8601171.3****(22) Date of Filing 20.01.1988****(71) Applicant(s)****WMS (UK) Limited****(Incorporated in the United Kingdom)****Brookfoot Mills, Elland Road, BRIGHOUSE,
West Yorkshire, HD6 2RW, United Kingdom****(72) Inventor(s)****Stephen Camm****(74) Agent and/or Address for Service****Urquhart-Dykes & Lord (Home Counties)
8th Floor, Tower House, Merlion Way, LEEDS,
LS2 8PA, United Kingdom****(51) INT CL⁶****E05C 9/04****(52) UK CL (Edition O)****E2A AAK A138 A180 A172 A192 A507****(56) Documents Cited****GB 2167208 A GB 2148377 A EP 0685353 A1
EP 0223582 A1****(58) Field of Search****UK CL (Edition O) E2A AAK AMXJ
INT CL⁶ E05C 9/02 9/04****(54) Espagnolette mechanism**

(57) An espagnolette mechanism 10 comprises a gearbox 11 having a gear 13 mounted for rotation in the gearbox 11 under the action of the rotary input 12, a rack 14 in mesh with the gear 13, a sliding rail 15 coupled with the rack 14 and capable of linear reciprocation upon rotation of the gear 13, a locking projection 23 carried by the rail 15 and moveable between locking and release positions with respect to a fixed keeper on the fixed frame, upon movement of the rail 15. A second rail 16 is connected to a slave pinion 17 by drive pins 18, 20 and an operating arm 21 such that it moves in the opposite direction to rail 15. The rails 15, 16 are slidably mounted on a fixed mounting rail 24 which is adapted to mount the espagnolette mechanism 10 on the face of a frame member of an openable frame.

**FIG. 1****FIG. 2**

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

GB 2 309 256 A